

Phone: 0294-2470837, 0294-2471056 (Fax), E-mail: ctaedean@gmail.com COLLEGE OF TECHNOLOGY AND ENGINEERING

Maharana Pratap University of Agriculture & Technology, Udaipur – 313 001 Rajasthan

No. CTAE/ECE/Tender/2023/_26/

Dated: 16-01-2023

NOTICE INVITING LIMITED BIDS

BID Ref. No.: CTAE/ECE/2023/LB- 0 9

Dated: 16.01.2023

Sealed Bids, in prescribe format, are invited on behalf of the Dean, College of Technology and Engineering, Maharana Pratap University of Agriculture and Technology, Udaipur (Rajasthan) for the procurement of Goods (and related services)/ Services/Work as listed below and detailed in the Schedule of Supply (Annexure-1), from manufacturers/distributors/ authorised dealers/ stockiest/ registered Bidders/ bona-fide dealers up to the Date and Time Specified below. The Bidders or their representative may be present in the bid opening. This bidding document may also be downloaded from our websites www.ctae.ac.in or www.mpuat.ac.in or the website of State Public Procurement Portal www.mpuat.ac.in

IMPORTANT BID DATA

1.	Procuring Entity's address for Bid Submission, clarification, and Opening of Bids	Dean, College of Technology and Engineering, Administrative Block, Udaipur - 313 001 Telephone No.: 0294-2470837; Fax No.: 0294-2471056, E-mail: ctaedean@gmail.com		
2.	Deadline for Bid submission	Date: 27-01-2023	Time: 4.00 PM	
3.	Bid opening	Date: 28-01-2023	Time: 11.00 AM	
5.	Bid Security Amount	Rs. 3990/-		
6.	Bid Should remain Valid Up to	30 Days from the Last date of submission of Bids		

Brief Description of the Goods/ Services/Works:

(Please Refer to the Schedule of Supply (Annexure-1) for Detailed Specifications and

Special Conditions, if any)

SN	Name of the Goods/ Services/Works	Quantity and Unit	Approx. Cost* (Rs.)
1.	Function Generator	04	108550/-
	DC Power Supply (0-30 V/2A , 5V/2A, 0 to +/- 15V/1A)	04	91000/-

^{*}Including all taxes and expenditure.

TERMS & CONDITIONS:

1. Bid Preparation and Submission:

1.1 The bid/quotation must be submitted on official letter head of the bidder in the enclosed format (Annexure-1) and signed by the Bidder and must be properly sealed in an envelope. On the envelope "Bid for the Supply of [Name of Item/Services.]", "Due date of Opening" and Bid Ref. No. must be clearly marked. If the bid is not sealed and marked as required, the Procuring Entity shall assume no responsibility about its consequences including misplacement and premature opening of the Bid.

Validity of Quotation: 2.

Quotation shall remain valid for acceptance for a period not less than 30 days after the deadline date specified for submission.

Bid prices 3.

- 3.1 The rates quoted by the bidder shall be in Indian Rupees only and shall remain fixed for the duration of the contract and shall not be subject to adjustment on any account.
- 3.2 All taxes like Central/ Rajasthan GST, etc. to be charged extra should be shown separately (along with their rate) failing which the rates quoted by the bidder shall be assumed to be inclusive of all taxes and levies.
- 3.3 All rates quoted must be FOR destination (CTAE, Udaipur) and should include all incidental charges.
- 3.3 The goods quoted should be as per the required specifications. Any deviations should be mentioned in the quotations.
- 3.4 Wherever applicable, the Make and Model No. of goods offered and their technical leaflet/brochure must invariably be enclosed, failing which the bid may be rejected.

Award of Contract/Supply Order 4.

- The Purchaser will award the contract/Supply Order to the bidder whose quotation has been determined to be substantially responsive, conform to the terms & conditions, and specifications and who has offered the lowest evaluated quotation price.
- Notwithstanding the above, the Purchaser reserves the right to accept or reject any quotations and to cancel the bidding process and reject all quotations at any time prior to the award of contract.

General 5.

- 5.1 Quantities given are approximate and the final order may be placed for more or less quantities.
- 5.2 The bids for the items, wherever indicated, will not be accepted without samples.
- 5.3 In all future references the Bid No. must be invariably mentioned.
- 5.4 Normal commercial warranty/ guarantee shall be applicable to the supplied goods.
- 5.5 The bidder has to mention their RST/CST/GSTIN No. in their quotations otherwise their bids are liable to be rejected.
- 5.6 Payment shall be made against printed, pre-receipted, and pre-stamped invoice/bill mentioning RST/CST/GSTIN No.

Copy to:

1. Dr. B.L Salvi, Nodal Officer (Accounts), with a soft copy in pdf format to kindly arrange to unload the Bid Document on the College website and the State Public Procurement Portal.

2. The S.O. (A/C)

3. The tenders Notice Board.

Annexure-1

FORMAT OF QUOTATION

a submitted on the Letter head of the Bidder)

S.N. Name of the Goods/ Services/Works with Specifications (including installation requirements, if any) (2) (3) (4) (5) Function Generator: Features & Technical Specifications: 10 MHz Function Generator with Arbitrary Waveforms AM,FM,PM,FSK Modulation and Built-in 200MHz Frequency Counter ,DDS technology Single-channel output 125MSa/s Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications • DC Output: A: 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B: 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit: 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (±15 V) • Resolution: Voltage: 100 mV Current: 100 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rose is ≤ 1 mVrms •	(To be submitted on the Letter head of the Blader) Taxes and						
Specifications (including installation requirements, in any) (In Fig. and Words) (In Fig. a		10 00 submitted with	Unit	Quoted Unit	Taxes and		
Specifications (including installation requirements, in any) (In Fig. and Words) (In Fig. a	S.N.	Name of the Goods/ Services/ Works with		Rate in Rs.			
(1) (2) (3) (4) (5) Function Generator: Features & Technical Specifications: 10 MHz Function Generator with Arbitrary Waveforms AM,FM,PM,FSK Modulation and Built-in 200MHz Frequency Counter ,DDS technology Single-channel output 125MSa/s Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B: 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit : 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution : Voltage : 100 mV Current : 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for voltage &		Specifications (including installation requirements, in					
(2) (3) (4) (5) Function Generator: Features & Technical Specifications: 10 MHz Function Generator with Arbitrary Waveforms AM,FM,PM,FSK Modulation and Built-in 200MHz Frequency Counter ,DDS technology Single-channel output 125MSa/s Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this DC Power Supply (0-30V/2A,5V/2A, 0 to +/- 15V/1A) Peatures & Technical Specifications • DC Output: A: 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B: 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit: 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (±15 V) • Resolution: Voltage: 100 mV Current: 100 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 100 mA • Ripple & Rip					included)		
(1) (2) Function Generator: Features & Technical Specifications: 10 MHz Function Generator with Arbitrary Waveforms AM,FM,PM,FSK Modulation and Built-in 200MHz Frequency Counter ,DDS technology Single-channel output 125MSa/s Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B ∴ 5 V, 2 A adjustable from 4 V - 6 V C :0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit : 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution : Voltage : 100 mV Current : 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : 10 mVrms • Display : 3 digit for 10 mVrms • Display : 3 digit for 10 mVrms • Displa		any)			(5)		
Function Generator: Features & Technical Specifications: 10 MHz Function Generator with Arbitrary Waveforms AM,FM,PM,FSK Modulation and Built-in 200MHz Frequency Counter ,DDS technology Single-channel output 125MSa/s Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this 2 DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications • DC Output: A: 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B: 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit: 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (±15 V) • Resolution: Voltage: 100 mV Current: 100 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: 4 mVrms • Display:		(2)	(3)	(4)	(5)		
Function Generator: Features & Technical Specifications of Sample Rate Frequency Counter ,DDS technology Single-channel output 125MSa/s Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this 2 DC Power Supply (0-30V/2A,5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications of Coarse and Fine controls B, continuously variable by means of Coarse and Fine controls B: 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual Tracking adjustable of Current Limit: 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) of Resolution: Voltage: 100 mV Current: 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: ≤ 1 mVrms of Display: 3 digit for 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Ripple & Noise: 100 mV Current: 100 mA of Rippl	(1)	2) & Technical Specifications:	04		2		
AM,FM,PM,FSK Modulation and Bullt-III 200thut 125MSa/s Counter ,DDS technology Single-channel output 125MSa/s Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B : 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit : 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution : Voltage : 100 mV Current : 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for		Function Generator: Features & Technical Specifications	122000	Fig			
Counter ,DDS technology Single-chainler output wave forms, Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this 2 DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Peatures & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B : 5 V, 2 A adjustable from 4 V - 6 V C:0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit : 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (±15 V) • Resolution : Voltage : 100 mV Current : 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: 100 mA •	1	10 MHz Function Generator Will Arolling Frequency		1.6.			
Counter ,DDS technology Single-chainler output wave forms, Sample Rate Frequency resolution 1mHz Display 4" colour LCD Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this 2 DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Peatures & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B : 5 V, 2 A adjustable from 4 V - 6 V C:0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit : 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (±15 V) • Resolution : Voltage : 100 mV Current : 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mA • Ripple & Noise: 100 mA •	1.	AM,FM,PM,FSK Modulation and Built-in 2007/112 125MSa/s					
Sample Rate Frequency resolution 11112 Display Vertical resolution 14 bits 5 types of standard output waveforms, and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B : 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit : 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution : Voltage : 100 mV Current : 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: 10 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: 10 mVrms • Display : 3 digit for 10 mA • Ripple & Noise: 10 mVrms • Display : 3 digit for 10 mVrms • Display : 3 digi	1	Counter ,DDS technology Single-Chainer output 12Dienlay 4" colour LCD					
Vertical resolution 14 bits 5 types of standard output waveforms and built-in 40 Arbitrary waveforms Modulation functions: AM, FM, PM, FSK, sweep, burst in this 2 DC Power Supply (0-30V/2Å, 5V/2Å, 0 to +/- 15V/1Å) 2 Features & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B : 5 V, 2 Å adjustable from 4 V - 6 V C:0 - ±15 V, 1 Å Dual Tracking adjustable • Current Limit : 100 mÅ - 2 Å continuously adjustable for (0-30 V & 5 V) 100 mÅ - 1 Å continuously adjustable for (± 15 V) • Resolution : Voltage : 100 mV Current : 100 mÅ • Ripple & Noise: ≤ 1 mVrms • Display : 3 digit for 100 mÅ • Ripple & Noise: ≤ 1 mVrms • D				Words:			
and built-in 40 Arbitrary Waveforms Modulation (Arbitrary Waveforms Modulation (Arbitrary Waveforms Modulation (Arbitrary Waveforms (Arbitrary Waveforms)) PM, FSK, sweep, burst in this FM, PM, PM, PM, PM, PM, PM, PM, PM, PM, P							
FM, PM, FSK, sweep, burst in this DC Power Supply (0-30V/2A, 5V/2A, 0 to +/- 15V/1A) Features & Technical Specifications • DC Output : A : 0-30 V, 2 A, continuously variable by means of Coarse and Fine controls B : 5 V, 2 A adjustable from 4 V - 6 V C :0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit : 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution : Voltage : 100 mV Current : adjustable for (± 15 V) • Resolution : Voltage : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mA • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Display : 3 digit for 10 mX • Ripple & Noise : ≤ 1 mVrms • Ripple & Noise : ≤ 1 mVrms • Ripple & Noise : ≤ 1 mVrms • Ripple & Nois	1	and built-in 40 Arbitrary Wavelorius Woddiation Tanton					
DC Power Supply (0-30 V/ 2A, 3 V/2A, 0 to V/2A, 5 V/2A, 0 to V/2A, 2 A continuously variable by means of Coarse and Fine controls B : 5 V, 2 A adjustable from 4 V - 6 V C:0 - ±15 V, 1 A Dual Tracking adjustable • Current Limit: 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution: Voltage: 100 mV Current: adjustable for (± 15 V) • Resolution: Voltage: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for				Fig.			
Features & Technical Specifications • DC Output: TY: A, continuously variable by means of Coarse and Fine controls B : 5 V, 2 A adjustable from 4 V - 6 V C: 0 - ±15 V, 1 A Dual : Tracking adjustable • Current Limit: 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution: Voltage: 100 mV Current: adjustable for (± 15 V) • Resolution: Voltage: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digit for 10 mA • Ripple & Noise: 3 digi	2	DC Power Supply (0-30 V/2A, 5 V/2A, 0 to 1/2 13 V/11)	lightern.				
A, continuously variable by means of Coalse and Thie experience of the Coa	1-						
: 5 V, 2 A adjustable from 4 V - 6 V C to 4 15 V, Tracking adjustable • Current Limit: 100 mA - 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution: Voltage: 100 mV Current: adjustable for (± 15 V) • Resolution: Object of the fore current I ED indication for voltage &							
Tracking adjustable • Current Limit: 100 in A = 2 A continuously adjustable for (0-30 V & 5 V) 100 mA - 1 A continuously adjustable for (± 15 V) • Resolution: Voltage: 100 mV Current: adjustable for (± 15 V) • Resolution: Voltage: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mV				Words:			
adjustable for (0-30 V & 5 V) 100 mA = 1 A continue adjustable for (± 15 V) • Resolution: Voltage: 100 mV Current: 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for		1 1 1 1 - Current I imit ' IIII IIIA - 2 A Continuous J	1				
adjustable for (± 15 V) • Resolution: Voltage: 100 in V current. 10 mA • Ripple & Noise: ≤ 1 mVrms • Display: 3 digit for 10 mA • D		1 11 C (0.20 \/ \frac{1}{27} \frac{1}{2} \frac{1}{2} \	1				
10 mA • Ripple & Noise: ≤ 1 m v ms • Display . 3 digit lot		The Decolition Vollage . 100 lift Cultone .					
		The state of the s					
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
Glowing 'ORA' or 'ORB', 'ORC' or ORC' ELD's material		Glowing 'ORA' or 'ORB', 'ORC' or ORC' LLD'S material					
Overload • Short circuit protection		Overload • Short circuit protection					

DECLARATION

- (a) I/We declare that I am/ we are Manufacturers/ Whole sellers/ Sole distributor/ Authorized dealer/ bonfire dealers in the Goods and Related Services or Services/Works for which I/We have Bid.
- (b)I/We agree to supply the above goods/Services in accordance with the technical specifications within the period specified in the Bidding Documents. I/We further agree that our rates, if approved, shall remain valid for further 2 or 3 months from the Last Date of Submission of Quotations.
- (c) We also confirm that the normal commercial Warrantee/Guarantee of At least 12 months shall apply to the offered goods.
- (d) I/We have not been debarred by the State Government or the Procuring Entity.
- (f) If this declaration is found to be incorrect or I/We fail to supply the goods/services, then without prejudice to any other action that may be taken, the Supply Order/Bid, if any to the extent accepted, may be cancelled and I/We may be debarred from participating in future bids as per rules.

Signature of Bidder Name & Address of Bidder:				
	Magazania a de a commissión à sider			
Contact No				
PAN No				
GST No				